

Safety Data Sheet

All Models Powerlets

Section 1: Identification

Product Name:

Crosman Powerlet

Synonyms:

Compressed CO2, Carbon Dioxide

CAS Number:

124-38-9

Product Use:

Propellant

Manufacturer:

Crosman Corporation

Address: 7629 State Route 5 & 20

Bloomfield, New York 14469

General Information Phone Number:

(585) 657-6161

Transportation Emergency Number:

CHEMTREC: 800-424-9300

Date of Preparation/Revision:

January 1, 2014

Section 2: Hazard Identification

Physical State:

Gas

Emergency Overview:

WARNING!

CONTENTS UNDER PRESSURE.

MAY CAUSE RESPIRATORY TRACT, EYE, AND SKIN IRRITATION. CAN CAUSE TARGET

ORGAN DAMAGE.

Do not puncture or incinerate container.

Can cause rapid suffocation. Avoid breathing gas. Use with

adequate ventilation.

contact with rapidly expanding gas can cause

frostbite.

GHS label elements

The substance is classified and labelled according to

the Globally Harmonized System (GHS).

Hazard pictograms



GHS03 Gas Cylinder

Signal word

Warning

Hazard Statement

H280 - Contains gas under pressure; may explode if

heated

Precautionary statements

P410+P403 - Protect from sunlight. Store in a well-

ventilated place

Potential acute health effects

Eyes:

Moderately irritating to eyes.

Contact with rapidly expanding gasses may

cause burns or frostbite.

Skin:

Moderately irritating to skin.

Contact with rapidly expanding gasses may

cause burns or frostbite.

Inhalation:

Moderately irritating to respiratory system.

Ingestion:

Ingestion is not a normal route of

exposure for gases.

Potential chronic health effects

Carcinogenic Effects: Mutagenic Effects: Teratogenic Effects:

Not available Not available

Not available

Medical Conditions aggravated by

over-exposure:

Pre-existing disorders involving any target organs mentioned above as being at risk may be aggravated by over-exposure to this

product.

Section 3:	Composition				
	Name	CAS Number	%		

Carbon Dioxide

<u>CAS Number</u> 124-38-9 % Volume 100

Section 4: First Aid Measures

Eyes:

Frostbite:

Check for and remove contact lenses.

Immediately flush eyes with copious amounts of water for at least 15 minutes,

occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin: In case of contact, flush skin with copious

amounts of water for at least 15 minutes.

Seek medical attention immediately.

Try to warm up the frozen tissues and

seek medical attention.

Inhalation: Move exposed person to fresh air. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as collar, tie, belt

or waistband. Seek medical attention

immediately.

Ingestion:

As this product is a gas, refer to the

inhalation section.

Section 5: Fire Fighting Measures

Flammability of Product:

Non-Flammable

Combustion Products:

Decomposition products may include the

following materials:

carbon dioxide

carbon monoxide

Suitable Extinguishing Media:

Use an extinguishing agent that is suitable

for the surrounding fire.

Fire-Fighting Procedures

Apply water or other suitable extinguishing agent from a safe distance to cool the

container and protect surrounding area.

Unusual Fire and Explosion Hazards:

Contains gas under pressure. In a fire or if

heated, a pressure increase will occur and the container may burst or explode.

Section 6: Accidental Release Measures

Personal Protection:

Use suitable protective equipment.

Environmental Precautions:

Discard any product in an environmentally

acceptable manner, in compliance with all

federal, state and local regulations.

Section 7: Handling and Storage

Handling

Use good hygiene practices. Wash hands before eating, drinking or smoking.

Keep away from heat and flame.

Do not puncture container.

Storage

Store in a cool, dry, well-ventilated area away from heat and sources of ignition.

Protect against physical damage.

Storage temperature should not exceed

52°C (125°F).

Section 8: Exposure Controls / Personal Protection

Exposure Limits ACGIH TLV (US 1/2008)

STEL: 54000 mg/m³ 15 minutes STEL: 30000 ppm 15 minutes TWA: 9000 mg/m³ 8 hours

TWA: 5000 ppm 8 hours NIOSH REL (US, 6/2008)

STEL: 54000 mg/m³ 15 minutes

STEL: 30000 ppm 15 minutes TWA: 9000 mg/m³ 10 hours TWA: 5000 ppm 10 hours

OSHA PEL (US, 11/2006)

TWA: 9000 mg/m³ 8 hours

TWA: 5000 ppm 8 hours OSHA PEL 1989 (US, 3/1989)

STEL: 54000 mg/m³ 15 minutes STEL: 30000 ppm 15 minutes TWA: 18000 mg/m³ 8 hours TWA: 10000 ppm 8 hours

Engineering Controls

Personal Protection - Eyes Personal Protection - Skin Use with adequate ventilation.

Wear appropriate safety glasses/goggles.
Personal protective equipment for the body should be selected based upon the tasks being performed and the risks associated

with those tasks.

Personal Protection - Respiratory

No special protection required under normal

product usage.

Personal Protection - Hands

Personal protective equipment for the body should be selected based upon the tasks being performed and the risks associated

with those tasks.

	200		1 -1 1	
Section	0.	Dhycical	and Chemica	Il Dronortioc
Section	J.	FIIVSICUI	una chemica	I FIUDELLIES

Molecular Weight:

Molecular Formula:

Boiling/condensation point:

Melting/freezing point:

Critical Temperature:

Vapor Pressure: Vapor Density:

Specific Volume (ft³/lb):

Gas Density (lb/ft³):

44.01 g/mole

CO2

-78.6°C (-109.5°F)

Sublimation Temperature: -78.6°C (-109.5°F)

30.9°C (87.6°F)

830 (psig)

1.53 (Air = 1)

8.7719 0.114

Section 10: Stability and Reactivity

Stability and Reactivity

Hazardous decomposition

This product is stable

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Hazardous Polymerization

Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11: Toxicological Information

Target Organs:

May cause damage to the following organs:

lungs, cardiovascular system, skin, eyes,

central nervous system (CNS).

Routes of Entry:

Inhalation

Toxicity Data

Product/ingredient name: carbon dioxide

Result

Species

Dose

Exposure

LC50 Inhalation Gas

Rat

470000 ppm

30 minutes

IDLH:

40000 ppm

Chronic effects on humans:

May cause damage to the following organs:

lungs, cardiovascular system, skin, eyes,

central nervous system.

Carcinogenic effects:

None known

Mutagenic effects:

None known

Reproductive effects:

None known

Section 12: Ecological Information

Aquatic ecotoxicity:

Not available

Products of Degradation:

Not available

Environmental fate:

Not available

Environmental Hazards:

No known significant effects or critical hazards.

Toxicity to the environment:

Not available

Section 13: Disposal Considerations

Product must be disposed of in accordance with all appropriate Federal, State,

and local regulations.

Section 14: Transport Information

United States

DOT Classification

UN Number:

UN1013

Proper Shipping Name:

CARBON DIOXIDE

Class:

Not Applicable (gas)

Packing Group:

o c , (pp.::cab.c (8as)

Label:

2.2

UN Number:

UN2187

Proper Shipping Name:

Carbon dioxide, refrigerated liquid

Class:

2.2

Packing Group:

Not Applicable (gas)

Label:

2.2

2.2

Canada

TDG Classification

UN Number:

UN1013

Proper Shipping Name:

CARBON DIOXIDE

Class:

2.2

Packing Group:

Not Applicable (gas)

Label:

2.2

UN Number:

UN2187

Proper Shipping Name:

Carbon dioxide, refrigerated liquid

Class:

2.2

Packing Group:

Not Applicable (gas)

Label: 2.2

Mexico

UN Number: UN1013

Proper Shipping Name: CARBON DIOXIDE

Class: 2.2

Packing Group: Not Applicable (gas)

<u>Label:</u> 2.2

UN Number: UN2187

Proper Shipping Name: Carbon dioxide, refrigerated liquid

Class: 2.2
Packing Group: Not Applicable (gas)

Label: 2.2

Section 15: Regulatory Information

United States

U.S. Federal Regulations:

United States inventory (TSCA 8b):

This material is listed or exempted.

SARA 302/304/311/312 Extremely Hazardous

Substances: No products were found SARA 302/304 Emergency Planning and Notification: No products were found.

SARA 302/304/311/312 Hazardous Chemicals:

carbon dioxide

SARA 311/312 MSDS distribution - chemical

inventory - hazard identification:

carbon dioxide: sudden release of pressure, immediate (acute) health hazard, delayed

(chronic) health hazard.

Clean Water Act (CWA) 307:

No products were found.

Clean Water Act (CWA) 311:

No products were found.

Clean Air Act (CAA) 112 accidental release

prevention:

No products were found.

Clean Air Act (CAA) 112 regulated flammable

substances:

No products were found.

Clean Air Act (CAA) 112 regulated toxic

substances:

No products were found.

State Regulations:

Connecticut Carcinogen Reporting:

This material is not listed.

Connecticut Hazardous Material Survey:

This material is not listed.

Florida Substances:

This material is not listed.

Illinois Chemical Safety Act:

This material is not listed.

Illinois Toxic Substances Disclosure to

Employee Act:

This material is not listed.

Louisiana Reporting:

This material is not listed.

Louisiana Spill:

This material is not listed.

Massachusetts Spill:

This material is not listed.

Massachusetts Substances:

This material is not listed.

Michigan Critical Material:

This material is not listed.

Minnesota Hazardous Substances:

This material is not listed.

New Jersey Hazardous Substances:

This material is not listed.

New Jersey Spill:

This material is not listed.

New Jersey Toxic Catastrophe Prevention Act:

This material is not listed.

New York Acutely Hazardous Substances:

This material is not listed.

New York Toxic Chemical Release reporting:

This material is not listed.

Pennsylvania RTK Hazardous Substances:

This material is not listed.

Rhode Island Hazardous Substances:

This material is not listed.

Canada

WHMIS:

Class A: Compressed Gas.

CEPA Toxic Substances:

This material is not listed.

Canadian ARET:

This material is not listed.

Canadian NPRI:

This material is not listed.

Alberta Designated Substances:

This material is not listed.

Ontario Designated Substances:

This material is not listed.

Quebec Designated Substances:

This material is not listed.

Section 16: Other Information

United States Label Requirements:

GAS:

CONTENTS UNDER PRESSURE. CAUSE
RESPIRATORY TACT, EYE, AND SKIN
IRRITATION. CAN CAUSE TARGET ORGAN

DAMAGE.

Do not puncture or incinerate container.


Can cause rapid suffocation.

Canada Label Requirements:

Class A: Compressed Gas.

Hazardous Material Information

System (U.S.A.):



Note:

To the best of our knowledge, the information contained in this document is accurate. No liability is assumed for the accuracy or completeness of the information contained

in this document.

All materials may present unknown hazards and should be used with caution.

Although certain hazards have been noted in this document, there is no guarantee that these