



Remington Arms Company, Inc.
 PO Box 700; 870 Remington Drive
 Madison, NC 27025
 800.243.9700

PRODUCT DATA SHEET

Product .. 12-Ga. 2¾" Action-proving (functional) Dummy
 Index Not applicable
 RAMAC 20581
 Date prepared 27-July-06

COMPONENT & MANUFACTURING INFORMATION

GAUGE/BORE 12-Gauge 2¾" shell length.
SHELL CONSTRUCTION "Unibody" clear (natural) plastic body with low black oxide steel head.
PAYLOAD WEIGHT 492 grains (1¹/₈ ounces), nominal.
PAYLOAD DESCRIPTION 2% Antimonial #2 lead shot.
PRIMER None; head is formed with either:
 - no primer pocket, flat on base, or
 - hemispherical dimple where the primer would normally be located.
PRIMER SEALANT Not applicable.
CASEMOUTH CONFIGURATION.. Folded crimp.
HEADSTAMP..... Loaded cartridges are headstamped with the following information: "REMINGTON" and "12 GA"
PROPELLANT DETECTION Dummy round; no propellant used; not applicable.
LOT IDENTIFICATION Each box of ammunition is identified with a code which allows traceability to shift/day/month/year of packaging and/or loading and all in-process assembly and test results.
FINAL INSPECTION 100% visual and/or vision system inspection of finished shells prior to final packaging.
PACKAGING Box quantity25 shells
 Case Quantity 250 shells

BALLISTIC & PERFORMANCE INFORMATION

INSTRUMENTAL VELOCITY..... Not applicable.
MUZZLE ENERGY..... Not applicable.
CHAMBER PRESSURE Not applicable.



The product described on this data sheet is manufactured by Remington Arms Company, Inc. at their ammunition production facility in Lonoke, Arkansas. This facility is registered to the standards of ISO-9001:2000