




Remington Arms Company, Inc.  
 PO Box 700, 870 Remington Drive  
 Madison, NC 27025  
 800.243.9700

**PRODUCT DATA SHEET**

Product ..... 40 S&W/141-gr JIC  
 Index ..... FE40SW1  
 RAMAC ..... 28360  
 Date prepared/ revised ..... 13-May-03

**COMPONENT & MANUFACTURING INFORMATION**

**CALIBER** ..... 40 S&W  
**SHELL**..... Brass (Copper alloy 260; cartridge brass)  
**BULLET WEIGHT** ..... 141-grain  
**BULLET CONSTRUCTION** ..... Brass jacketed, compressed powdered iron core, frangible  
**PRIMER** ..... Remington #149-HMF (1½-HMF); Diazodinitrophenol (Dinol)-based heavy-metal-free priming mix. Operating range -40° F to +150° F (-40° C to +66° C)  
**PRIMER SEALANT** ..... None  
**CASEMOUTH SEALANT** ..... Asphaltic sealant  
**CASE KNURL** ..... None  
**HEADSTAMP**..... Loaded cartridges are headstamped with the following information: “R-P” and “40 S&W”  
**PRIMER MARKING** ..... Primer cups are marked “HF” to enable visual identification   
**PROPELLANT DETECTION** ..... 100% mechanical, electrical, or electro-mechanical detection of propellant level within the cartridge.  
**LOT IDENTIFICATION** ..... Each box of ammunition is identified with a unique code which allows traceability to shift/day/month/year of packaging and/or loading and all in-process assembly and test results.  
**FINAL INSPECTION** ..... 100% visual and/or vision system inspection of finished cartridges prior to final packaging.  
**PACKAGING** ..... Box quantity .....50 cartridges  
 Case Quantity .... 500 cartridges

**BALLISTIC & PERFORMANCE INFORMATION**

**AVERAGE INSTRUMENTAL VELOCITY** ..... 1,135 ± 35 fps (measured at 15’, over 20’) for a 10-round test when fired from a SAAMI-compliant test barrel.  
**AVERAGE PRESSURE** ..... 35,000 psi maximum for a 10-round test measured at the time of manufacture with a conformal piezoelectric transducer in a SAAMI-compliant test barrel.  
**AVERAGE MUZZLE ENERGY** .... 403 ft-lb<sub>f</sub>  
**ACCURACY** ..... Maximum extreme spread of three 5-round groups of 3.1” at 25 yards fired from a SAAMI-compliant accuracy test barrel mounted in a Universal Receiver.  
**BULLET PULL** ..... Minimum average (10-round test) ..... 72 lb<sub>f</sub>  
 Minimum individual ..... 59 lb<sub>f</sub>